


VOLTAGE-MODE PWM CONTROLLER

The KA7500B is used for the control circuit of the pulse width modulation switching regulator. The KA7500B consists of 5V reference voltage circuit, two error amplifiers, flip flop, an output control circuit, a PWM comparator, a dead time comparator and an oscillator. This device can be operated in the switching frequency of 1 KHz to 300 KHz.

FEATURES


- Internal regulator provides a stable 5V reference supply trimmed to 1 %
- Uncommitted output TR for 200mA sink or source current
- Output control for push-pull or single-ended operation
- Variable duty cycle by dead time control (pin 4)
- Complete PWM control circuit
- On-chip oscillator with master or slave operation
- Internal circuit prohibits double pulse at either output



ORDERING INFORMATION

Device	Package	Operating Temperature
KA7500B	16 DIP	0 ~ + 70°C
KA7500BD	16 SOP	0 ~ + 70°C

BLOCK DIAGRAM



ABSOLUTE MAXIMUM RATINGS

Characteristic	Symbol	Value	Unit
Supply Voltage	V_{CC}	42	V
Collector Supply Voltage	V_C	42	V
Output Current	I_O	250	mA
Amplifier Input Voltage	V_{IN}	$V_{CC} + 0.3$	V
Power Dissipation ($T_A = 25^\circ\text{C}$)	P_D	1 (KA7500B) 0.9 (KA7500BD)	W
Operating Temperature Range	T_{OPR}	$0 \sim +70$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-65 \sim +150$	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS

($V_{CC} = 20\text{V}$, $f = 10\text{KHz}$, $T_A = 0^\circ\text{C}$ to $+70^\circ\text{C}$, unless otherwise specified)


Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
REFERENCE SECTION						
Reference Output Voltage	V _{REF}	I _{REF} = 1mA	4.75	5.0	5.25	V
Line Regulation	ΔV _{REF}	V _{CC} = 7V to 40V		2.0	25	mV
Temperature Coefficient of V _{REF}	ΔV _{REF} /ΔT	T _A = 0℃ to 70℃		0.01	0.03	%/℃
Load Regulation	ΔV _{REF}	I _{REF} = 1mA to 10mA		1.0	15	mV
Short-Circuit Output Current	I _{SC}	V _{REF} = 0	10	35	50	mA
OSCILLATOR SECTION						
Oscillation Frequency	f	C _T = 0.01 μF, R _T = 12KΩ		10		KHz
Frequency Change with Temperature	Δf/ΔT	C _T = 0.01 μF, R _T = 12KΩ			2	%
DEAD TIME CONTROL SECTION						
Input Bias Current	I _{BIAS}	V _{CC} = 15V, 0V < V ₄ < 5.25V		-2.0	-10	μA
Maximum Duty Cycle	D _(MAX)	V _{CC} = 15V, V ₄ = 0V O.C Pin = V _{REF}	45			%
Input Threshold Voltage	V _{ITH}	Zero Duty Cycle		3.0	3.3	V
		Max. Duty Cycle	0			
ERROR AMP SECTION						
Input Offset Voltage	V _{IO}	V ₃ = 2.5V		2.0	10	mV
Input Offset Current	I _{IO}	V ₃ = 2.5V		25	250	mA
Input Bias Current	I _{BIAS}	V ₃ = 2.5V		0.2	1.0	μA
Common Mode Input Voltage	V _{CM}	7V < V _{CC} < 40V	-0.3		V _{CC}	V
Open-Loop Voltage Gain	G _{VO}	0.5V < V ₃ < 3.5V	70	95		dB
Unit-Gain Bandwidth	BW			650		KHz

ELECTRICAL CHARACTERISTICS(V_{CC} = 20V, f = 10KHz, T_A = 0°C to + 70°C, unless otherwise specified)


Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
PWM COMPARATOR SECTION						
Input Threshold Voltage	V _{ITH}	Zero Duty Cycle		4	4.5	V
Input Sink Currnet	I _{SINK}	V ₃ =0.7V	-0.3	-0.7		mV
OUTPUT SECTION						
Output Saturation Voltage Common Emitter	V _{CE(SAT)}	V _E = 0, I _C = 200mA		1.1	1.3	V
Common Collector	V _{CC(SAT)}	V _C = 15V, I _E = -200mA		1.5	2.5	
Collector Off-State Currnet	I _{C(OFF)}	V _{CC} = 40V, V _{CE} = 40V		2	100	μA
Emitter Off-State Current	I _{E(OFF)}	V _{CC} = V _C = 40V, V _E = 0			-100	
TOTAL DEVICE						
Supply Current	I _{CC}	Pin 6 = V _{REF} , V _{CC} = 15V		6	10	mA
OUTPUT SWITCHING CHARACTERISTIC						
Rise Time	t _R					
Common Emitter				100	200	nS
Common Collector				100	200	
Fall Time	t _F					
Common Emitter				25	100	nS
Common Collector				40	100	

TYPICAL APPLICATION


PLUSE WIDTH MODULATED STEP-DOWN CONVERTER



Dimensions in Millimeters



16-SOP-225



16-SOP-225A

