

Thermal Line TM-L60II

EPSON®



Fast, Quiet Label Printer

Versatile Printing

The ideal printer for small-scale POS applications. Capable of printing label serial numbers and fence and ladder bar codes.

Space-Saving, Easy-To-Use Design

Advantages of this ultra-compact model include automatic paper positioning, -way cable connection, and an on-board ESC/POS®-based command system.

Smooth and scalable character printing capability.

Print method		Thermal line
Print font	Font	9 x 24/12 x 24
	Column capacity (columns)	42/32 (Roll paper) 40/30 (Label)
	Character size (mm)	0.99(W) x 3.39 (H)/1.41(W) x 3.39(H)
	Character set	95 Alphanumeric, 32 International, 128x7 Graphic, Barcode:UPC-A, UPC-E, JAN13 (EAN), JAN8 (EAN), CODE39, CODE93, CODE128, ITF, CODABAR
	Character Per Inch	20.0 CPI/15.0 CPI
Interfaces		RS-232/Bi-directional parallel
Data buffer		4k bytes or 45 bytes
Print speed		12 LPS (with 1/6" paper feed), 50 mm/sec.
Paper	Dimensions (mm)	Roll paper:60.0 + 0/-1(W) x dia.83.0, Label:60+0.2/-0.5 (W) x dia.83.0
	Thickness (mm)	Label:143 ± 15µm
Power		24 VDC±7%
Power consumption		Approx. 1.0A (mean)
D.K.D. function		2 drivers
Reliability		MTBF: 18x10 ⁴ hours MCBF: 29x10 ⁶ lines (thermal paper), 12x10 ⁶ lines (thermal label)
Overall dimensions (mm)		123(W)x201(D)x124(H)
Weight (Approx.)		0.8Kg
EMC standards		VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Power supply		PS-170 (option)
Safety standards		UL/CSA/TÜV (EN60950)