

9-pin, serial dot **TM-U300 Series**

EPSON®



Comprehensive PC-POS Printers

Speedy Receipt Printing

Offering logic seeking control enabling speedy 3.5 LPS for 40 columns and 5.8 LPS for 20 columns in black or red. All from lightweight, small footprint units ideal for PC-POS tasks.

Print method		9-pin, serial impact dot matrix
Print font	Font	7x9/9x9
	Column capacity (columns)	40/33
	Character size (mm)	1.24(W) x 3.1(H)/1.56(W) x 3.1(H)
	Character set	95 Alphanumeric, 32 International, 128x7 Graphic
	Character Per Inch	16 CPI/13.3 CPI
Interfaces		RS-232/Bi-directional parallel
Data buffer		1k bytes or 40 bytes (serial I/F), 1K byte or 0 bytes (parallel I/F)
Print speed		3.5 LPS (at 40 columns), 5.8 LPS (at 20 columns)
Paper	Dimensions (mm)	76.0 ± 0.5(W) x dia.83.0,
	Thickness (mm)	0.06 to 0.085
Copy capability		One original and two copies
Inked ribbon		ERC-38 (red/black, purple, black)
Ribbon life		B/R:15 x 10 ⁵ characters (black), 75 x 10 ⁴ characters (red) Purple: 4 x 10 ⁶ characters, Black: 3 x 10 ⁶ characters
Power		AC adapter (included)
Power consumption		Approx. 33W
D.K.D. function		2 drivers
Reliability		MTBF: 18 x 10 ⁴ hours MCBF: 18 x 10 ⁶ lines
Overall dimensions (mm)		A:170(W) x 288(D) x 183(H), B:170(W) x 253(D) x 148(H) C:158(W) x 297(D) x 145(H), D:158(W) x 235(D) x 125(H)
Weight (Approx.)		A:2.8Kg, B:2.6Kg, C:1.6Kg, D:1.6Kg
EMC standards		VCCI class A, FCC class A, CE marking
Power supply		Exclusive AC adapter (included)
Factory options		Wall-hanging bracket WH-10 (B and D types)
Safety standards		UL/CSA/TÜV (AC adapter only)