

# 9-pin, serial dot **TM-U590**

**EPSON®**



## **Wide Slip Printer**

### **Multi-Application Capability**

Designed to satisfy virtually any printing requirements including slips up to 88 columns wide. Printing of one original with four copies also possible.

### **Easy Operation**

High-speed, bi-directional, logic-seeking printer with the ESC/POS® command system for smooth, easy operation. Automatic Status Back function for printer operation status confirmation.

<b>Print method</b>		9-pin, serial impact dot matrix
<b>Print font</b>	Font	7x9 / 9x9
	Column capacity (columns)	88/66
	Character size (mm)	1.3(W) x 3.1(H)/1.6(W) x 3.1(H)
	Character set	95 Alphanumeric, 32 International, 128x10 Graphic
	Character Per Inch	16.7 CPI/ 12.5 CPI
<b>Interfaces</b>		RS-232/Bi-directional parallel, RS-485 (dealer option)
<b>Data buffer</b>		4k bytes or 69 bytes
<b>Print speed</b>		311CPS/233 CPS
<b>Paper</b>	Dimensions (mm)	70(W) x 70(L) to 210(W) x 257(L)
	Thickness (mm)	0.09 to 0.2 (total thickness: 0.36)
<b>Copy capability</b>		One original and four copies
<b>Inked ribbon</b>		ERC-31 (purple)
<b>Ribbon life</b>		Purple: 7 x 10 <sup>6</sup> characters, Black: 4.5 x 10 <sup>6</sup> characters
<b>Power</b>		24VDC ± 10%
<b>Power consumption</b>		Approx. 1.9A(mean)
<b>D.K.D. function</b>		2 drivers
<b>Reliability</b>	MTBF: 18 x 10 <sup>4</sup> hours	
	MCBF: 29 x 10 <sup>6</sup> lines	
<b>Overall dimensions (mm)</b>		252(W) x 266(D) x 185(H)
<b>Weight (Approx.)</b>		5Kg
<b>EMC standards</b>		VCCI Class A, FCC class A, CE marking, AS / NZS 3548 class B
<b>Power supply</b>		PS-170 (option)
<b>Safety standards</b>		UL/CSA/TÜV (EN60950)