

9-pin, serial dot TM-U675

EPSON®



Durable, Multi-Purpose Printer

Fast & Ultra-Quiet

Bi-directional minimum distance printing assures high-speed throughput. Quieter than other impact dot printers of its class.

Convenient Features

Two-way paper loading possible. Automatic Status Back (ASB) function automatically transmits changes in printer status.

Print method		9-pin, serial impact dot matrix
Print font	Font	5x9 / 7x9
	Column capacity (columns)	Receipt: 37/50, Slip / Validation: 45/60
	Character size (mm)	1.56(W) x 3.1(H)/1.24(W) x 3.1(H)
	Character set	95 Alphanumeric, 32 International, 128x8 Graphic
	Character Per Inch	13.3 CPI/ 17.8 CPI
Interfaces		RS-232/Bi-directional parallel / RS-485 (dealer option) / USB
Data buffer		4k bytes or 45 bytes
Print speed		Approx. 4.6 LPS (at 40 columns, 17.8 CPI)
Paper	Dimensions (mm)	Roll paper: 82.5 ± 0.5(W) x dia.83.0, Slip: 70(W) x 150(L) to 148(W) x 210(L), Validation: 148(W) x 70(L) to 150(W) x 210(L)
	Thickness (mm)	Roll paper: 0.06 to 0.085 (total tickness: 0.09 to 0.31 Slip:0.09 to 0.2 (total thickness: 0.09 to 0.31)
Copy capability		One original and two copies
Inked ribbon		ERC-32 (purple)
Ribbon life		6 x 10 ⁶ characters
Power		24VDC ± 10%
Power consumption		Approx. 1.8A (mean)
D.K.D. function		2 drivers
Reliability		MTBF: 18 x 10 ⁴ hours
		MCBF: 37 x 10 ⁶ lines
Overall dimensions (mm)		186(W) x 298(D) x 195(H)
Weight (Approx.)		5.8Kg
EMC standards		VCCI class A, FCC class A, CE marking, AS / NZS3548 class B
Power supply		PS-170 (option)
Factory option		MICR device
Safety standards		UL/CSA/TÜV(EN60950)